

Get A Superior Seal, In A Flash.

Marco delivers everything you need to seal pipes securely. From a huge variety of Master Flash® RoofBoots to expandable edge strip for awkward flashing shapes and surfaces. With Marco as your one-stop-shop, you'll get the roof flashing you need quickly, and rest easy knowing you're getting industry-leading warranties and Weather-Tite performance.



UNIVERSAL ROOFBOOT

**ROUND
FLEXIBLE SLEEVE**

The proven choice with a 20-year warranty.

- Easy, on-site customization for superior fit
- Sleeve flexibility absorbs vibration and pipe movement caused by expansion/contraction
- Maximum resistance to ozone weathering
- Available in black or grey EPDM, red or grey silicone, or colors upon request



Specs

Ozone Resistance: 70 hrs @ 500pphm (EPDM and RS)*

High Temp. Resistance:

Intermittent: +135°C/+275°F (EPDM), +260°C/+500°F (RS)

Continuous: +100°C/+212°F (EPDM), +225°C/+437°F (RS)

Low Temp. Resistance:

-55°C/-67°F (EPDM),

-74°C/-101°F (RS)

Compression Set:

25% (EPDM), 50% (RS)

*RS = Red Silicone

| | Pipe Range | Base |
|------|-----------------|------------------|
| Mini | 0" - 3/4" | 4" (101 mm) |
| #1 | 1/4" - 2 1/2" | 3 1/4" (82 mm) |
| #2 | 1 3/4" - 3" | 6 1/4" (158 mm) |
| #3 | 1/4" - 5" | 7 3/4" (196 mm) |
| #4 | 3" - 6 1/4" | 9 1/4" (234 mm) |
| #5 | 4 1/4" - 7 3/4" | 10 1/2" (266 mm) |
| #6 | 5" - 9" | 13" (330 mm) |
| #7 | 6" - 11" | 14 1/2" (368 mm) |
| #8 | 7" - 13" | 16 1/2" (412 mm) |
| #9 | 9" - 19" | 25 1/4" (641 mm) |

The Marco Weather-Tite™ System

Closure

Ventilation

Fasteners

Flashing

Sealants

Underlayment

Accessories



Our flashing products are made of EPDM or silicone and compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light. As part of the exclusive Marco Weather-Tite System, they offer easy installation, superior performance, and tremendous value.

You may also need



Marco's Weather-Tite™
Metal Roof Sealant



Fasteners